



19.10.2025, 04:33

## VOLVO FH 500 6x2 FASSI F545R.A.2.25 CRANE KRAN NEW !!!









**Price:** €235 000

#### **Attributes**

**Emission standard:** Euro 6 **Drive configuration:** 6x2

Transmission type: automatic Production year: 2025

Przebieg: 1 km Moc silnika: 500 KM

# **Specifications**

#### ID:504

- 1. Volvo FH D13 500 WB4900 6x2 chassis
- 6x2 drive
- · Front pneumatic axle 9000 kg
- · Rear bogie cushion 23000 kg first drive axle 13 tons, second hydraulically steered axle 10 tons,
- · Technical weight of the set 50000 kg
- · Frame reinforced along the entire length (inner insert 5mm) · D13 500kM Euro 6 phase E

#### engine,

- · VEB+ engine brake,
- · I-shift automatic gearbox, one crawler gear,
- · Rear axle without hub reduction ratio 2.64
- · Rear coupling fi 40mm Rockinger,
- · Wheelbase 4900mm,
- · FH sleeper cab with standard height,
- · Gray color silver gray,
- · Two benches,
- · Two heated air-suspension comfort seats 1+1,
- · Webasto dry 2 kW, refrigerator in the cabin,
- · Leather multi-function steering wheel,
- · Rich set of instruments,
- · Reversing camera and blind spot camera with additional multimedia display,
- · EC 4.0 tachograph
- · Preparation for CB and FMS communication,
- · 6 LED work lamps,
- · Front and rear main LED lamps,
- · Rooster warning lamps on the roof,
- · Central locking with remote control,
- · Axle load indicator,
- · Front collision warning system with electronic brake,
- 2. Fassi F545RA.2.25 crane mounted behind the cabin
- · 5 hydraulic arms
- 5/6 function
- · Unlimited 360 degree rotation
- · Support legs rotated 180 degrees in 7790 mm spacing
- · Additional support legs in 4984 mm spacing
- · Radio control with Start/Stop control and engine speed control
- FSC H control system, which controls stability and manages lifting functions depending on the support spacing
- · LS variable displacement hydraulic pump,
- · Crane adapted to mount the boom
- · Winch preparation mounting plate, 7th hydraulic section and remote control.
- · OPTION 2T or 3T winch, the winch can work with the crane alone or with the crane and boom.
- · OPTION additional hydraulic arms (maximum 8 arms)
- · OPTION additional manual arms, · OPTION additional boom (maximum 6 hydraulic arms)
- 3. Fixed body
- External body approx. 6350mm, external width 2550mm (inside approx. 6275mm, internal width 2480mm)
- · Twist Lock fastenings in the floor for
- · Steel front wall 1000mm high chain and sling holders,

- · 25mm removable aluminum rear board 800mm high,
- · 25mm aluminum side boards 800mm high,
- · Removable side boards divided into 3,
- · Two 800mm removable middle and rear posts,
- 9 cargo handles in the plating per side load capacity 3 tons each,
- · Floor made of 24mm thick non-slip plywood,
- · Road load capacity approx. 7.5 tons

### **Contact**

Name: Piotr Adamczyk Name: Łukasz Glica

**Phone:** +48 696 325 819 **Phone:** +48 604 267 087

**Email:** piotr.adamczyk@starsanduo.pl **Email:** lukasz.glica@starsanduo.pl

Name: Sylwia Lis - Kończak Name: Damian Banasik

**Phone:** +48 532 575 246 **Phone:** +48 698 629 201

Email: sylwia@starsanduo.pl Email: damian.banasik@starsanduo.pl